PC11

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 21/10/2011 Revision date: 02/07/2026 Supersedes: 25/01/2024 Version: 2.8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : PC11
UFI : KF6W-40G5-P00S-3WQ4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Intended for general public
Main use category : Consumer use,Professional use

1.3. Details of the supplier of the safety data sheet

Pittsburgh Corning Europe Inc.
Albertkade 1
BE 3980 Tessenderlo
België
T +32 (0) 13 66 17 21, F +32 (0) 13 667 854
www.foamglas.com

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

CLP Signal word : Warning

Hazard statements (CLP) : H226 - Flammable liquid and vapour.
Precautionary statements (CLP) : P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground and bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	methanol (67-56-1)
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	methanol (67-56-1)

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component	
Substance(s) not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	n-butyl acetate (123-86-4)

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
n-butyl acetate substance with national workplace exposure limit(s) (BE, GB)	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29	<18	Flam. Liq. 3, H226 STOT SE 3, H336
methanol substance with national workplace exposure limit(s) (BE, FR, GB, NL, CH); substance with a Community workplace exposure limit	CAS-No.: 67-56-1 EC-No.: 200-659-6 EC Index-No.: 603-001-00-X REACH-no: 01-2119433307-44	<2	Flam. Liq. 2, H225 Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Dermal), H311 (ATE=300 mg/kg bodyweight) Acute Tox. 3 (Oral), H301 (ATE=100 mg/kg bodyweight) STOT SE 1, H370
Quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, chlorides	CAS-No.: 61789-72-8 EC-No.: 263-081-3 REACH-no: 01-2119970169-28	<0.3	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Corr. 1, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 2, H411

Specific concentration limits:		
Name	**Product identifier**	**Specific concentration limits (%)**
methanol	CAS-No.: 67-56-1 EC-No.: 200-659-6 EC Index-No.: 603-001-00-X REACH-no: 01-2119433307-44	(3 ≤ C < 10) STOT SE 2; H371 (10 ≤ C < 100) STOT SE 1; H370

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : If medical advice is needed, have product container or label at hand.
First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact : IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical advice if skin irritation persists.
First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion : Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Get medical advice/attention if you feel unwell.
Symptoms/effects after inhalation : Inhalation may cause irritation, cough, shortness of breath. May cause headache and dizziness. May cause drowsiness or dizziness. Obtain medical attention if breathing difficulty persists.
Symptoms/effects after skin contact : Remove all contaminated clothing and footwear. IF ON SKIN: Wash with plenty of soap and water. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact : Irritating to eyes. Rinse immediately with plenty of water for 15 minutes. Consult a doctor.
Symptoms/effects after ingestion : Swallowing of this material presents health hazard. May cause lung damage if swallowed. Seek a medical assistance, even if there are no immediate symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Show this safety data sheet to the doctor or emergency department.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : hazy water, carbon dioxide (CO2), foam and powder.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Heating may cause a fire or explosion.
Explosion hazard : May form flammable/explosive vapour-air mixture.

5.3. Advice for firefighters

Precautionary measures fire : Evacuate area.
Firefighting instructions : Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting : Self-contained breathing apparatus. Complete protective clothing. Do not attempt to take action without suitable protective equipment.
Other information : Use water spray or fog for cooling exposed containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate every possible source of ignition. No naked flames, sparks, and do not smoke.

For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene. Do not get in eyes, on skin, or on clothing. Use personal protective equipment - see point 8. Limit spread.

For emergency responders

Protective equipment	:	Equip cleanup crew with proper protection. Do not attempt to take action without suitable protective equipment.
Emergency procedures	:	Ventilate area.

6.2. Environmental precautions

Notify authorities if liquid enters sewers or public waters. Collect spillage.

6.3. Methods and material for containment and cleaning up

For containment	:	Collect spillage.
Methods for cleaning up	:	Liquid is absorbed with granules or similar. Collect in suitable containers. Rinse thoroughly with water. Further handling of spillage - see point 13. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible.
Other information	:	Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	:	Use only outdoors or in a well-ventilated area. Eliminate all ignition sources if safe to do so. Wear personal protective equipment. Do not get in eyes, on skin, or on clothing. Take precautionary measures against static discharge.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	:	Use only non-sparking tools. Take precautionary measures against static discharge.
Storage conditions	:	Keep cool. Store in a well-ventilated place. Keep container tightly closed.
Storage area	:	Store away from direct sunlight or other heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

methanol (67-56-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOELV TWA (mg/m³)	260 mg/m³
IOELV TWA (ppm)	200 ppm
Belgium - Occupational Exposure Limits	
Local name	Alcool méthylique # Methanol
Limit value [mg/m³]	266 mg/m³
Limit value [ppm]	200 ppm
Short time value [mg/m³]	333 mg/m³
Short time value [ppm]	250 ppm

methanol (67-56-1)	
Remark (BE)	D: la mention “D” signifie que la résorption de l’agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l’exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l’agent dans l’air. # D: de vermelding “D” betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
France - Occupational Exposure Limits	
VME [mg/m³]	260 mg/m³
VME [ppm]	200 ppm
VLE [mg/m³]	1300 mg/m³
VLE [ppm]	1000 ppm
Switzerland - Occupational Exposure Limits	
VME [mg/m³]	260 mg/m³
VLE [mg/m³]	1040 mg/m³

n-butyl acetate (123-86-4)	
Belgium - Occupational Exposure Limits	
Local name	Acétate de n-butyle # n-Butylacetaat
Limit value [mg/m³]	238 mg/m³
Limit value [ppm]	50 ppm
Short time value [mg/m³]	712 mg/m³
Short time value [ppm]	150 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023

DNEL and PNEC

Bitumen (8052-42-4)	
DNEL/DMEL (Workers)	
Long-term - local effects, inhalation	2.88 mg/m³
DNEL/DMEL (General population)	
Long-term - local effects, inhalation	0.61 mg/m³

siliciumdioxide, amorf (7631-86-9)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, inhalation	4 mg/m³
Long-term - local effects, inhalation	0.963 mg/m³

methanol (67-56-1)	
DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	20 mg/kg bw/day
Acute - systemic effects, inhalation	130 mg/m³
Acute - local effects, inhalation	130 mg/m³
Long-term - systemic effects, dermal	20 mg/kg bw/day
Long-term - systemic effects, inhalation	130 mg/m³

methanol (67-56-1)	
Long-term - local effects, inhalation	130 mg/m³
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	4 mg/kg bw/day
Acute - systemic effects, inhalation	26 mg/m³
Acute - systemic effects, oral	4 mg/kg bw/day
Acute - local effects, inhalation	26 mg/m³
Long-term - systemic effects,oral	4 mg/kg bw/day
Long-term - systemic effects, inhalation	26 mg/m³
Long-term - systemic effects, dermal	4 mg/kg bw/day
Long-term - local effects, inhalation	26 mg/m³

calciumcarbonaat (471-34-1)	
DNEL/DMEL (Workers)	
Long-term - local effects, inhalation	6.36 mg/m³
DNEL/DMEL (General population)	
Acute - systemic effects, oral	6.1 mg/kg bw/day
Long-term - systemic effects,oral	6.1 mg/kg bw/day
Long-term - local effects, inhalation	1.06 mg/m³
PNEC (STP)	
PNEC sewage treatment plant	100 mg/l

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:
During spraying wear suitable respiratory equipment.

Personal protection equipment

Personal protective equipment:
Gloves.
Personal protective equipment symbol(s):



Eye and face protection

Eye protection:
In case of risky circumstances: safety glasses or face shield

Skin protection

Skin and body protection:
Use personal protective equipment as required.

Hand protection:
Nitrile-rubber protective gloves

Respiratory protection

Respiratory protection:
Ventilation, local exhaust, or breathing protection. High gas/vapour concentration: gas mask with filter type A

Environmental exposure controls

Environmental exposure controls:
Avoid release to the environment.
Other information:
Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	Black.
Appearance	:	Paste.
Odour	:	Characteristics.
Odour threshold	:	Not available
Melting point	:	Not available
Freezing point	:	Not available
Boiling point	:	Not available
Flammability (solid, gas)	:	Not available
Lower explosive limit (LEL)	:	Not available
Upper explosive limit (UEL)	:	Not available
Flash point	:	37 °C
Auto-ignition temperature	:	Not available
Decomposition temperature	:	Not available
pH	:	Not available
Viscosity, kinematic	:	Not available
Solubility	:	Not available
Log Kow	:	Not available
Vapour pressure	:	Not available
Vapour pressure at 50°C	:	Not available
Density	:	1.21 kg/l (20°C)
Relative density	:	Not available
Relative vapour density at 20°C	:	Not available
Particle characteristics	:	Not applicable

9.2. Other information

Other safety characteristics

VOC content	:	207 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Heating may cause a fire or explosion.

10.2. Chemical stability

Combustible liquid.

10.3. Possibility of hazardous reactions

All heat sources, including direct sunlight. Avoid fire and sparks. Remove all sources of ignition. Avoid shocks and friction.

10.4. Conditions to avoid

Avoid shock and friction.

10.5. Incompatible materials

Bases. Acids. Oxidising agents.

10.6. Hazardous decomposition products

Fire may liberate carbon oxides (CO) and smoke.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

Quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, chlorides (61789-72-8)	
LD50 oral	344 mg/kg
LD50 dermal rat	3413 mg/kg

methanol (67-56-1)	
LD50 oral rat	> 5000 mg/kg
LD50 oral	5628 mg/kg bodyweight
LD50 dermal rabbit	15800 mg/kg
LD50 dermal	15800 mg/kg bodyweight
LC50 Inhalation - Rat	85 mg/l/4h
LC50 Inhalation - Rat [ppm]	64000 ppm/4h
LC50 Inhalation - Rat (Dust/Mist)	85000 mg/l

Skin corrosion/irritation : Not classified (Based on available data, the classification criteria are not met)

methanol (67-56-1)	
pH	No data available in the literature

Serious eye damage/irritation : Not classified (Based on available data, the classification criteria are not met)

methanol (67-56-1)	
pH	No data available in the literature

Respiratory or skin sensitisation : Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure : Not classified (Based on available data, the classification criteria are not met)

methanol (67-56-1)	
STOT-single exposure	Causes damage to organs (central nervous system, eyes).

n-butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

methanol (67-56-1)	
Viscosity, kinematic	0.685 – 0.743 mm²/s

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short–term (acute) : Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long–term (chronic) : Not classified (Based on available data, the classification criteria are not met)

Quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, chlorides (61789-72-8)	
LC50 fish 1	0.1 mg/l
EC50 Daphnia 1	0.059 mg/l
EC50 72h - Algae [1]	0.11 mg/l

methanol (67-56-1)	
LC50 fish 1	15400 mg/l (96 h; Lepomis macrochirus)
LC50 fish 2	10800 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 1	> 10000 mg/l (48 h; Daphnia magna)
EC50 Daphnia 2	24500 mg/l (48 h; Daphnia magna)
EC50 other aquatic organisms 1	10000 mg/l waterflea
EC50 other aquatic organisms 2	12000 mg/l
EC50 96h - Algae [1]	22000 mg/l OECD 201: Algae: Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Freshwater, Experimental value, Growth rate
Threshold limit other aquatic organisms 1	6600 mg/l (16 h; Pseudomonas putida)
Threshold limit algae 1	530 mg/l (192 h; Microcystis aeruginosa)
Threshold limit algae 2	8000 mg/l (168 h; Scenedesmus quadricauda)

12.2. Persistence and degradability

PC11	
Persistence and degradability	Rapidly degradable

Quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, chlorides (61789-72-8)	
Persistence and degradability	Rapidly degradable

methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.6 – 1.1 g O_2/g substance
Chemical oxygen demand (COD)	1.4 g O_2/g substance
ThOD	1.5 g O_2/g substance

n-butyl acetate (123-86-4)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

methanol (67-56-1)	
BCF fish 1	< 10 (72 h; Leuciscus idus)
BCF fish 2	1 (72 h; Cyprinus carpio)
Log Pow	-0.77

methanol (67-56-1)	
Bioaccumulative potential	Low bioaccumulation potential.

12.4. Mobility in soil

methanol (67-56-1)	
Surface tension	0.023 N/m (20 °C)
Log Koc	-0.89 – -0.21 log Koc, Calculated value
Ecology - soil	Very mobile in the soils.

12.5. Results of PBT and vPvB assessment

PC11
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	methanol (67-56-1)
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	methanol (67-56-1)

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

PC11	
Other information	Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Discharging into rivers and drains is forbidden. Dispose of in accordance with relevant local regulations.

Additional information : Flammable vapours may accumulate in the container. Clean up even minor leaks or spills if possible without unnecessary risk.

Ecology - waste materials : Avoid release to the environment.

European List of Waste (LoW, EC 2000/532) : 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances

HP Code : HP3 - “Flammable:”
– flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
– flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
– flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
– flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
– water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
– other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
HP5 - “Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:” waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.

SECTION 14: Transport information

In accordance with ADR / IMDG / ADN / RID

ADR	IMDG	ADN	RID
14.1. UN number or ID number			
Not regulated for transport			
14.2. UN proper shipping name			
Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No
Not applicable (cf. 2.2.3.1.5)			

14.6. Special precautions for user

Overland transport
Transport regulations (ADR) : Not applicable (cf. 2.2.3.1.5)

Transport by sea
Transport regulations (IMDG) : Not applicable (cf. 2.2.3.1.5)

Inland waterway transport
Transport regulations (ADN) : Not applicable (cf. 2.2.3.1.5)

Rail transport
Transport regulations (RID) : Not applicable (cf. 2.2.3.1.5)

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Not listed on the Ozone Depletion list (Regulation EU 2024/590)
Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 207 g/l

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

National regulations

Denmark

Class for fire hazard : Class II-1
Store unit : 5 liter
Classification remarks : R10 <H226>; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with it.
If an employee is pregnant or breastfeeding and the person in question uses or is exposed to this product at work, the employer must always carry out a risk assessment of the work. The assessment must both deal with the dangerousness of the impact and its strength and duration. The employer's decision that a pregnant or lactating woman can perform a specific work task must therefore be made in the context of her specific working conditions. See also WEA-Guideline A.1.8-7 on the working environment of pregnant and breastfeeding workers.
Listed or contains substance(s) on the Denmark - Indicative list of organic solvents present in Annex 3.4.1 of the WEA Guidance C.0.1-1: Methanol (67-56-1), Butyl acetate, all isomers (123-86-4)

Finland

France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK) : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1).
VOC content : 207 g/l

Poland

Polish National Regulations : Act of 25 February 2011 on chemical substances and their mixtures (J. o L. No. 63, item 322 as amended; consolidated text J. o L. 2019, item 1225).
Act of 14 December 2012 on waste (J. o L. 2013, item 322 as amended; consolidated text J. o L. 2020, item 797).
The announcement of Marshal of the Sejm of the Republic of Poland dated 19 October 2016 concerning the consolidated text announcement of the decree on the management of packaging and packaging waste (J. o L. 2016, item 1863 as amended).
Decree of the Minister of Environment of 14 December 2014 on the catalogue of waste (J. o L. 2014, item 1923).
Act of 19 August 2011 on the Carriage of Dangerous Goods (J. o L. 2011 No. 227, item 1367 as amended; consolidated text J. o L. 2020, item 154).
Regulation of the Minister of Family, Labour and Social Policy of 12 June 2018 on the highest permissible concentration and intensity of noxious agents for health at work environment (J. o L. item 1286 as amended).
The announcement of Minister of Health dated 9 September 2016 concerning the consolidated text announcement of the decree of the Minister of Health of 30 December 2004 on health and safety at work related to exposure to chemical agents at work (J. o L. of 16 September 2016, item 1488)
Regulation of the Minister of Health of 2 February 2011 on tests and measurements of the noxious agents for health at work environment (J. o L. No. 33, item 166 as amended).
Regulation of the Minister of Environment of 9 December 2003 on particularly hazardous substances to the environment (J. o L. No. 217, item 2141).
ADR Agreement: Government Statement of 13 March 2023 on the entry into force of amendments to Annexes A and B to the Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), signed in Geneva on 30 September 1957 (J. o. L. 2023, item 891)
Regulation of the Minister of Health of 25 August 2015 on the method of marking places, pipelines, and containers and tanks used for storing or containing hazardous substances or hazardous mixtures (J.o.L. 2015, item 1368 as amended)

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2

Full text of H- and EUH-statements:	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Corr. 1	Skin corrosion/irritation, Category 1
STOT SE 1	Specific target organ toxicity – single exposure, Category 1
STOT SE 2	Specific target organ toxicity – Single exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs.
H371	May cause damage to organs.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.