



DECLARATION OF PERFORMANCE
 DOP n° 140410300B 2019-01-01
FOAMGLAS® PERINSUL S



1. Unique identification code of the product-type	FOAMGLAS® PERINSUL S DOP n° 140410300B 2019/01/01-ThIB-CG-EN13167-PL(P)1-DS(70,90)-CS(Y)1800-BS550-TR200-WS-WL(P)-CC(1,5/1/50)500-Mu
2. Identification of the construction product as required under Art. 11(4)	Cellular glass - thermal break - FAB PERINSUL S
3. Intended use or uses of the construction product	Thermal insulation for buildings
4. Name and contact address of the manufacturer as required pursuant Art. 11(5)	PCE-Pittsburgh Corning Europe NV/SA - Albertkade 1 - B3980 Tessenderlo (B) www.foamglas.com quality-compliance@foamglas.com
5. Name of the authorised representative whose mandate covers the tasks specified in Art. 12(2)	none
6. System or systems AVCP as set out in Annex V	AVCP system 3
7. Harmonised standard	EN 13167 & ETA 18/0627 based on EAD 170018-00-0305
Notified body	Thermal conductivity - BBRI (No. 1136) & FIW (No. 751) / Fire reaction - WFGRT (No. 1173) / Compressive strength - BBRI (No. 1136)

8. Table 1

Essential characteristics	Performance	
	Thermal resistance	Thermal resistance (RD-value)
	Thermal conductivity (λD-value)	
	Thickness	
Reaction to fire Euroclass characteristics	Reaction to fire	
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal resistance (RD-value)	RD-value see table 2
	Thermal conductivity (λD-value)	
	Durability characteristics	Thermal conductivity of cellular glass products does not change with time, experience has shown the cell structure to be stable.
	Dimensional Stability	DS (70/90)
Durability of reaction to fire against heat, weathering, ageing/degradation	Durability characteristics	The fire performance of cellular glass does not deteriorate with time.
	Dimensional Stability	DS (70/90)
Compressive strength	Compressive strength	
	Point load	
Tensile/flexural strength	Bending Strength	
	Tensile strength parallel to faces	NPD
	Tensile strength perpendicular to faces	
Durability of compressive strength against aging degradation	Compressive creep	
Water permeability	Water absorption (short)	WS
	Water absorption (long)	WL(P)
Water vapour permeability	Water vapour resistance	∞ infinite
Acoustic absorption index	Sound absorption	AP1→NPD
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD
Continuous glowing combustion	Continuous glowing combustion	no glowing combustion

EN 13167:2012 + A1:2015

Table 2

Thickness (mm)	Thermal resistance (m²K / W)	Thickness (mm)	Thermal resistance (m²K / W)
40		125	
45		130	
50		135	
55		140	
60		145	
65		150	
70		155	
75		160	
80		165	
85		170	
90		175	
95		180	
100			
105			
110			
115			
120			

9. The performance of the product is in conformity with the declared performance. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer

Piet Vitse, European Director Norms & Standards, Product & Systems Certifications, Policy and Advocacy